



RFM700-M Series Refractometers

EASY TO USE INSTRUMENTS WITH AUTOMATIC TEMPERATURE COMPENSATION

FOR USE IN HARSH FACTORY ENVIRONMENTS

NEW



RFM700 series refractometers are robust, low cost, fully automatic instruments that are ideally suited to the food, sugar and beverage industries but can also be used in many other non-food applications where temperature control is not required.

Commonly, the RFM700-M series refractometers are supplied to operate in the °Brix scale with results temperature compensated to 20°C in accordance with ICUMSA. Additional user scales provide measurement in different formats such as Refractive Index (RI) various wine, urine specific gravity & automotive scales as well as allowing custom scales to be loaded in accordance with product data.

Inherent to the robust design is a sapphire prism mounted in an easy-clean stainless steel dish and an outer casing that is sealed and shaped to withstand sample spillage and moisture ingress. This, together with the external power supply and bright 4" high definition colour display, makes the RFM700-M ideal for use in busy laboratories or harsh factory environments. The instrument can also save and/or print results and be connected to a printer or laboratory PC, with results being output in standard print, CSV or secure PDF formats.




Other software features include special AG temperature compensation that facilitates a SPAN calibration when using AG calibration fluids, and a time delay before reading, ensuring reliable results every time.

- Classic red or modern colour display
- Auto-sense "hands free" measurement
- Simple audit trail (date, time & batch no.)
- Alpha-numeric keypad for easy data entry
- USB connectivity
- Flat sapphire prism surface for easy-cleaning
- Simple operation for factory environments



a xylem brand

RFM700-M Series of refractometers with automatic temperature compensation



Specifications	RFM712-M	RFM732-M	RFM742-M
Scales			
Refractive Index	1.32 - 1.42	1.32 - 1.54	1.32 - 1.54
Sugar (°Brix)	0 - 54	0 - 100	0 - 100
User Defined	100	100	100
Resolution			
Refractive Index	0.0001	0.0001	0.00001
Sugar (°Brix)	0.1	0.1	0.01
Accuracy			
Refractive Index	± 0.0001	± 0.0001	± 0.00004
Sugar (°Brix)	± 0.1	± 0.1	± 0.04
Precision (Reproducibility)*			
Refractive Index	± 0.00005	± 0.00005	± 0.00001
Sugar (°Brix)	± 0.05	± 0.05	± 0.01
User Scale Library	20+ pre-programmed scales including HFCS (3), Sugar (4), Honey, NaCl, Wine Must (5), Urine SG (3), Glycol (2), Urea, FSII and more; plus customer programmable user scales via PC.		
Reading Time	Minimum 4 seconds (dependent on precision required)		
Temperature Control	None - Temperature Compensation (ATC)		
Measuring Temperature Range	5 - 80 °C		
Temperature Sensor Accuracy	± 0.05 °C		
Temperature Compensation			
Sucrose (°Brix)	5 - 80 °C		
AG Fluid	5 - 40 °C		
User Defined	Simple coefficient (units/°C) or polynomial function		
Temperature Stability Checks	Programmable delay time		
Sample Illumination	Light Emitting Diode 589nm (100,000+ hours)		
Prism / Dish	Artificial Sapphire / Stainless Steel 316 / PEEK (spill barrier)		
Prism Seal	Silicone/Resin		
Interfaces	1 x USB (A), 1 x USB (B) - Ethernet & Serial (RS232) via optional adaptor		
Power	Instrument: 24 V DC, ±5%, <2A External PSU: 100-240V, 50-60Hz (supplied)		
Humidity Range	<90% RH (non condensing)		

Latest Software Features

- Easy to use Installation Wizard
- 7 Menu languages
- Save over 8000 readings
- Print to secure PDF
- Onboard user scale library
- User maintenance prompts

*for definitions, please visit our website

Order Codes

Code	Description
19-00	RFM712-M refractometer with latest integral 4" full colour display, robust switch membrane and USB connectivity. Supplied with instruction manual and certificate of conformity.
19-10	RFM732-M refractometer with latest integral 4" full colour display, robust switch membrane and USB connectivity. Supplied with instruction manual and certificate of conformity.
19-20	RFM742-M refractometer with latest integral 4" full colour display, robust switch membrane and USB connectivity. Supplied with instruction manual and certificate of conformity.



a xylem brand

International
Longfield Road
Tunbridge Wells
Kent, TN2 3EY
United Kingdom
Tel: +44 (0) 1892 500400
Fax: +44 (0) 1892 543115
sales.bs.uk@xylem-inc.com

United States
90 Horizon Drive
Suwanee
GA 30024
United States of America
Tel: 678 804 5730
Fax: 678 804 5729
sales.bs.us@xylem-inc.com

www.bellinghamandstanley.com